

OmniWise Pulsar Active AI Box 64GB



Overview

Ultimate AI Powerhouse for Mission-Critical Applications

When your projects require the absolute pinnacle of AI performance and memory capacity, Pulsar Active AI Box 64 GB module stands ready to meet the challenge. With twice the memory of the 32 GB variant, this module is built for the most demanding, mission-critical applications, such as autonomous vehicles, edge AI servers, and real-time analytics in complex environments. The expanded memory allows for the execution of the largest and most complex AI models, ensuring your system can handle extensive data processing with unmatched speed and precision, making it the ideal choice for the highest-stakes AI deployments.

- Support for NVIDIA Jetson AGX Orin and AGX Orin Industrial Module
- 2x USB 2.0 Type-A - 2x USB 3.2 Type-A
- 1x USB 2.0 Micro-B for recovery
- 1x GbE RJ-45 - 1x 10G RJ-45
- 1x HDMI 2.0 3840x2160 at 60Hz
- 1x UART, 1x SPI, 1x CAN, 2x I2C, 1x I2S, 5x GPIOs
- Active Heatsink
- Operating Temperature -25°C ~ +85°C
- Wide input voltage range from 9V to 36V DC
- 1x CAN bus with transceiver
- 1x Micro SIM socket


SPECIFICATIONS

Jetson Module	Jetson AGX Orin (32GB, 64GB or Industrial)	AI Performance	275 TOPS (INT8)
GPU	NVIDIA Ampere architecture with 2048 NVIDIA CUDA® cores and 64 tensor cores	CPU	12-core Arm Cortex-A78AE v8.2 64-bit CPU 3MB L2 + 6MB L3
Memory	64GB 256-bit LPDDR5 204.8GB/s	Dimensions	150 mm(L) x 137,5 mm(W) x 102,5 mm(H)
MISC / IO Connector	1x Micro SIM socket, 1x CAN bus with transceiver 40-pin (1x UART, 1x SPI, 1x CAN, 2x I2C, 1x I2S, 5x GPIOs)	USB	1x USB 2.0 Micro-B for recovery 2x USB 2.0 Type-A 2x USB 3.2 Type-A
DL Accelerator	2x NVDLA v2.0	Power Configuration	15W - 60W
Display Output	1x HDMI output	Wireless	1x M.2 E-Key
Networking	1x GbE RJ-45 - 1x 10G RJ-45	Input Power	12V-54V DC Input
Operating Temperature	-25°C to +85°C	Weight	2080 g (Including Antenna)
Video Encode	2x 4K60 4x 4K30 8x 1080p60 16x 1080p30 (H.265) H.264, AV1	Video Decode	1x 8K30 3x 4K60 7x 4K30 11x 1080p60 22x 1080p30 (H.265) H.264, VP9, AV1

Storage

1x micro-SD card slot 1x M.2 M Key SSD
(or AVerMedia capture card: CN311-H, CN312SW, CN312MW)

OmniWise Pulsar Active AI Box 64GB



Number	Name	Description
1	Fan	Active Cooling Airflow
2	Heatsink	Active Heatsink
3	Case	150mm(L) x 137,5mm(W) x 102,5mm(H) - 2080 g (Including Antenna)
4	Operating Temperature	-25°C to +85°C
5	DC Port	Voltage Range 12V - 54V
6	ETHERNET Port	1x 1 GbE RJ-45 ,1x 10 GbE RJ-45
7	USB Port	2x USB 3.0 Ports (Type-A)
8	HDMI Port	HDMI 2.0 (3840 x 2160 at 60Hz)
9	Multi - I / O Connector	40-pin (1x UART, 1x SPI, 1x CAN, 2x I2C, 1x I2S, 5x GPIOs)
10	Micro SIM	Micro SIM
11	Antenna Port	Antenna Port
12	USB Port	2x USB 2.0 Ports (Type-A)
13	CAN Bus	1x CAN Bus with Transceiver
14	Micro SD	Micro SD
15	Micro USB Port	USB 2.0 Micro-B
16	Recovery Button	Button for Recovery Mode
17	Power Button	Button for Power
18	DC - IN ATX	4-Pin 9V - 54V