



OmniWise Blanet AI Box ON 4GB

Overview

Utilizing the NVIDIA Jetson Orin Nano Module, the OmniWise AI Box offers an optimal solution for managing embedded IoT applications. Tailored for tasks like video analytics, robotics, and natural language processing, the OmniWise AI Box is adept at handling diverse applications. With a capacity to drive up to 100 TOPS, it delivers unparalleled AI performance and power efficiency, enhancing the capabilities of your projects significantly.



- 4 x USB 3.2 Gen1(5G) type A
- 1 x RJ-45 GbE port
- 40 pin (1× UART, 2× SPI, 2×I2C, 1×I2S, 6× GPIO)
- Wide input voltage range from 9V to 24V DC
- Operating Temperature 0°C to +70°C
- Fanless Design

SPECIFICATIONS

Jetson Module	Jetson Orin Nano 4GB	AI Performance	20 TOPS
GPU	512-core NVIDIA Ampere architecture GPU with 16 Tensor Cores	CPU	6-core Arm® Cortex®-A78AE v8.2 64-bit CPU 1.5MB L2 + 4MB L3
Memory	4GB 64-bit LPDDR5	Dimensions	120mm(L) x 92mm(W) x 90mm(H)
MISC / IO Connector	1x UART, 2x SPI 2x I2C, 1x I2S, 6x GPIOs	USB	1x USB 2.0 Micro-B for recovery 4 x USB 3.2 Gen 1 (5G) Type A
DL Accelerator		Power Configuration	7W - 10W
Display Output	1x HDMI 2.0	Camera Inputs	1x MIPI CSI-2 15 Pin
Networking	1x 10/100/1000 Base-T RJ45	Wireless	1x M.2 E-Key - 2230
Storage	1x NVME M.2 M-Key SSD - 2280	Input Power	9V-24V DC Input
Operating Temperature	0°C to +70°C	Weight	875g (Including Antenna)
Video Encode	1080p30 supported by 1-2 CPU cores	Video Decode	1x 4K60 (H.265) 2x 4K30 (H.265) 5x 1080p60 (H.265) 11x 1080p30 (H.265)

OmniWise

Blanet AI Box ON 4GB



Number	Name	Description
1	Heatsink	Passive Heatsink
2	Case	120mm(L) x 92mm(W) x 90mm(H) - 875g (Including Antenna)
3	HDMI Port	HDMI (3840 x 2160 at 60Hz)
4 - 5	USB Port	4x USB3.2 Gen1 (5G) type A
6	ETHERNET Port	GbE RJ-45
7	DC Port	Voltage Range 9V - 24V
8	Operating Temperature	0°C to +70°C
9	Multi - I / O Port	40-pin (1x UART, 2x SPI, 2x I2C, 1x I2S, 6x GPIO)
10	Micro USB Port	USB 2.0 Micro-B
11	Force Recovery Button	Button for Recovery Mode
12	Power Button	Button for Power
13	CSI Port	2 Lane MIPI CSI-2, 15 pin FPC 1mm Pitch Connector
14	Antenna Port	Antenna Port